

CONDUIT CABLE

Excellent elasticity and solid conduit cable, it provides smooth wire feeding without kinking, and it does not stretch and compress even after long-term use.

CONDUIT CABLE ASSY

Conduit can also be furnished cut to the desired length with a suitable adapter.

	IHCC-PP		IHCC-PA	
	FEEDER	PAILPACK	FEEDER	PAILPACK
ADAPER	PLUG	PLUG	PLUG	ADAPER
LENGTH	2, 3, 5m			



IHCC-PE (POLYETHYLENE)

FEATURES AND STRUCTURE

- PE conduit stranded with High tensile carbon steel wire protects soft wire and maintains shape even continuous flexing
- High-quality welding is possible with no metal sludge
- It is recommended to bend it more than 40cm radius
- SIZE : 4.0(I.D) x 9.0(O.D)



IHCC-FX (FLEXIBLE)

FEATURES AND STRUCTURE

- Stranded high-tensile carbon steel wire into steel plate coil conduit to remain flexible and maintain shape through repeated bending constructed to withstand the continuous flexing with automation It allows to bend into a very tight radius, but it is recommended to bend it more than a 25cm radius to maintain smooth wire feeding.
- Size : 4.0(I.D) X 9.0(O.D)



IHCC-EFX (EXTRA FLEXIBLE)

FEATURES AND STRUCTURE

- Extremely flexible conduit due to the application of steel plate coil
- It is electrically insulated with material for moving purpose, so it can be used for a long time even with continuous flexing associated with robot or automatic welding.
- It allows to bend into a very tight radius, to maintain smooth wire feeding, it is recommended to bend it more than a 15cm radius.
- Size : 6.0(I.D) X 11.0(O.D)


PAIL PACK CAP

It keeps the welding wire clean from dust, slag, spatter, and humid and leads safe and smooth wire feeding.



IHPPS-S/ IHPPS-L

- Easy to install without tools
- Flip window : a clear heat-resistant flip window that can be flipped up and viewed without removing the entire pail pack cap
- IHPPS-S : 510mm(Wire capacity : 200/250kg)
- IHPPS-L : 660mm (Wire capacity 300/400kg)



IHPPS-SC/IHPPS-LC

- Easy to install without tools
- Clear transparency Helps you to check the condition of the wire from any direction 360 degrees
- Flip window a clear heat-resistant flip window that can be flipped up and viewed 510mm without removing the entire pail pack cap
- IHPPS-S : (Wire capacity : 200/250kg)
- IHPPS-L : 660mm (Wire capacity 300/400kg)